



PELICAN™
BUILT TO PROTECT™

COUNT ON PELICAN FOR EMERGENCY LIGHTING

History repeats itself, especially when hurricanes are involved. That's why Pelican has developed the most extensive range of emergency lighting in the world. From Remote Area Lighting Systems (RALS) that shine through the night to safety approved lighting for use in hazardous environments- Pelican has the correct solution for first responders, law enforcement and industrial users.



2745



3315



3310



3415MCC



2765



2760



7607



2360



7607
Holster/Wand Kit



9480




9490




9410L



9430



30QT. Cooler



50QT. Cooler



70QT. Cooler

SPECIFICATIONS

HANDHELD FLASHLIGHTS AND HEADLAMPS

CAT NO.	BATTERIES	WEIGHT W/ BATTERIES (KG)	LENGTH (CM)	ANSI LIGHT OUTPUT	ANSI RUN TIME	ANSI BEAM DISTANCE (meters)	ANSI PEAK BEAM INTENSITY (candela)	ANSI WATERPROOF/ SUBMERSIBLE/ WATER RESISTANT	SAFETY CERTIFIED	COLORS
2360	2 AA Alkaline (Included)	5.4 oz (0.15)	6.2" (15.7)	375*, 29**	2h 30m*, 13h***	192*, 53***	9,187*, 705***	IPX8	N/A	■
2745	3 AAA Alkaline (Included)	3.3 oz. (0.1)	2.25" (5.7)	33*, 17***	20h*, 40h***	35*, 25***	309*, 155***	IPX4	CI D1 IECEX ia	■
2760	3 AAA Alkaline (Included)	3.4 oz. (0.1)	2.25" (5.7)	289*, 156**, 97***, 42****	1h 30m*, 3h 15m**, 5h 30m***, 11h****	101*, 66**, 48***, 19****	2540*, 1097**, 567***, 88****	IPX4	N/A	■
2765	3 AAA Alkaline (Included)	3.4 oz. (0.1)	2.25" (5.7)	132*, 78**, 155***, 34****	5h 30m*, 8h**, 6h 15m***, 14h****	68*, 46**, 81***, 10****	1157*, 529**, 1649***, 23****	IP54	CI D1 IECEX ia InMetro	■
3310	2 AA Alkaline (Included)	6.2 oz. (0.18)	6.14" (15.6)	378*, 39***	8h*, 202h***	196*, 62**	9,580*, 961***	IPX8	N/A	■ Photo Luminescent
3315	2 AA Alkaline (Included)	6.2 oz. (0.18)	6.14" (15.6)	160	19h	144	5153	IP67	CI II III D1 IECEX ia InMetro	■
3415MCC	4 NIMH Rechargeable (Included)	10.6 oz. (0.18)	7.51" (19.1)	183	5h	179	8,050	IPX7	CI II D2	■
7600	Rechargeable Lithium-Ion (Included) 	7.1 oz. (0.3)	6.19" (15.7)	944*, 479**, 37***	3h 15*, 4h 30m***, 9h 15m****	225*, 157**, 44*	12,693*, 6,172**, 480***	IPX8	N/A	■
9410L	07.4V, 6.6Ahr. Lithium-Ion (Included) 	44.7 oz. (1.27)	8.75" (22.2)	2207*, 463***	3h 15*, 11h***	43*, 207***	51,302**, 10,710***	IPX4	N/A	■

RALS (Remote Area Lighting Systems)

CAT NO.	BATTERIES (Included)	WEIGHT W/ BATTERIES (KG)	LENGTH (CM)	LUMENS	RUN TIME	BEAM SPREAD	NUMBER OF LEDs	LAMP HEADS	COLORS
9430	12v Rechargeable, Sealed Lead Acid (SLA) 	22.65 lbs (10.3)	32.28" (82) ^A	3000*, 1500**	up to 15h	125°	6	1	■
9480	12v Rechargeable, Sealed Lead Acid (SLA) 	27.5 lbs (12.47)	23.75" (60.3) ^A	4000, 3000**, 1000***	6h*, 8h** 28h***	125°	8 per head	1	■
9490	12v Rechargeable, Sealed Lead Acid (SLA) 	32 lbs (14.51)	72" (182.8) ^A	6000 (variable)	3h 30m*, 12h** 24h***	125°	10 per head	1	■

Pelican™ ELITE Coolers

CAT NO.	DESCRIPTION	INTERIOR DIMS (L X W X D)	EXTERIOR DIMS (L X W X D)	VOLUME	WEIGHT	HARDWARE
30 Qt. Elite Cooler	30 Qt. Elite Cooler	14.60" x 10.20" x 11.00" (37.1 x 25.9 x 27.9 cm)	25.30" x 19.00" x 18.50" (64.3 x 48.3 x 47 cm)	32.95 Qt. (31.18 Liters)	21.67 lbs. (9.8 kg)	Stainless steel
50 Qt. Elite Cooler	50 Qt. Elite Cooler	17.50" x 11.00" x 13.70" (44.5 x 27.9 x 34.8 cm)	30.00" x 20.30" x 20.40" (76.2 x 51.6 x 51.8 cm)	52.87 Qt. (50.03 Liters)	26.39 lbs. (12 kg)	Stainless steel
70 Qt. Elite Cooler	70 Qt. Elite Cooler	23.40" x 11.00" x 14.30" (59.7 x 27.9 x 36.3 cm)	36.00" x 20.30" x 21.00" (91.4 x 51.6 x 53.3 cm)	72.42 Qt. (68.53 Liters)	33.29 lbs. (15.1 kg)	Stainless steel

Additional approvals may apply. For details go to www.pelican.com



Rechargeable lights

* High
** Medium
*** Low

**** Downcast
A Extended Height

S Spot Beam
SD Spot & Downcast Beams

23215 Early Avenue, Torrance, CA 90505 • TEL 800.473.5422 • TEL 310.326.4700

©2022 Pelican Products, Inc. All trademarks are registered and/or unregistered trademarks of Pelican Products, Inc., its subsidiaries and/or affiliates. See Pelican.com/warranty for warranty details.

PELICAN.COM

DESIGNED IN

USA