

WATERTIGHT
PELI PROTECTOR CASES



LIFETIME GUARANTEE\*





Peli Cases Features	3
PELI CASE INTERIOR PROTECTION	4-5
PELI CASES	
Personal Utility Case Series	6
Memory Card & Micro Cases	7-8
Small Cases	9
_aptop & Tablet Cases	10-1
Medium Cases	12-13
Large Cases	14-17
Long Cases	18-19
Cases Specifications	20-2
Case Accessories	22-2

## **PELI CASES ALSO** MADE IN GERMANY

In line with the company's commitment to global sustainability, and to provide an improved customer experience, a large number of Peli Protector Case models are being manufactured at the Peli manufacturing facility in Crottendorf, Germany.

You will find all the models that apply marked with a "Made in Germany" logo in this catalogue. All other case models continue to be manufactured in the United States. The aim is to progressively expand the number of case models that are manufactured in Germany in the

Note that the dimensions of some cases manufactured in Germany differ slightly from the equivalent cases manufactured in the US. Please review the case dimensions carefully before initiating any project.



# PELI CASES FEATURES

Rugged, uncompromising and trusted, Peli cases protect what matters to you, from the everyday to the extraordinary. Peli Protector Cases are made with copolymer polypropylene and cutting edge technology, which makes them virtually indestructible and resistant to the most extreme conditions. Proven for over 45 years in the most demanding environments. Engineered and manufactured in the U.S and in Germany. Guaranteed for Life and sustainable due to its long life.

#### + STRONGER BY DESIGN

The Peli Protector Case™ uses an open cell core and solid wall construction, which is actually stronger and lighter than a solid core wall. Travel light with heavy protection. And you know it's a Peli™ Case by the distinctive dual band top surface. Stainless steel pins are used for hinges and handles. The Double-Throw latches are smarter and easier to open: it's the classic 'C' clamp design





with a secondary movement that works like a pry bar to start the release and offers plenty of leverage to open with a light pull.

#### + EASY RIDING

Stainless steel ball bearing wheels (on selected cases) last longer and ride smoother. The nylon hub adjacent to the stainless steel resists heat. Result: less wear and tear on the polyurethane tire.

- (1) NYLON HUB
- (2) STAINLESS STEEL **BALL BEARING WHEELS**
- (3) POLYURETHANE TIRE


#### + EXTRA PROTECTION



Peli's Pick N Pluck™ foam lets you customise the interior according to your gear. An easy, do-ityourself system: layers of foam are pre-scored in tiny cubes. Simply measure your equipment over the grid and pluck away.

#### + TESTED

The Peli™ Case design is the result of multiple generations of refinement. This evolution is proven through a battery of rigorous lab tests including drop, vibration, leak, heat and dust tests.



## + REINFORCED **PADLOCK PROTECTORS**

Stainless steel reinforced padlock protectors provide added strength and extra security against cutting and theft.



#### + WATERTIGHT

The secret is the tongue and groove fit with a polymer o-ring acting as a waterproof seal.



#### COOL UNDER PRESSURE

The Automatic Pressure Equalisation Valve releases built-up air pressure while keeping water molecules out, resulting in a watertight case that is even easier to open.



LEARN MORE AT WWW.PELICATALOGUE.COM/EN/PELI-PROTECTOR-CASI





# PELI CASE INTERIOR **PROTECTION**

Peli™ Cases are available empty or with any of the following protection solutions.

> Check how to install all accessories through our easy step-by-step Tutorial videos

+ CUSTOM FOAM SOLUTIONS

#### Made of simulated leather or ballistic nylon with nylon zippers. A wide variety of pocket sizes protect and keep your gear organised. They install easily with Velcro® strips (included).

+ LID ORGANISERS



	u	ID ORGANISER (	OPTIONS	
	MESH	COMPUTER	РНОТО	EMS
CASE	THE PARTY OF		HIE	
1430			1439 Photo A	
1440	1449 Mesh <sup>A</sup>			
1490		1498 Computer <sup>B</sup>		
1495		1495 Computer <sup>B</sup>		
1500	1509 Mesh		1508 Photo	1505 EMS <sup>B</sup>
1510	1519 Mesh <sup>A</sup>			
1520	1509 Mesh		1508 Photo <sup>B</sup>	
1550				1555 EMS <sup>B</sup>
1560	1569 Mesh			
1600	1609 Mesh <sup>B</sup>			1605 EMS A
1610	1609 Mesh <sup>B</sup>			
1620	1609 Mesh <sup>B</sup>			
1630	1639 Mesh <sup>A</sup>			
1640	0379 Mesh <sup>A</sup>			
1650	1659 Mesh <sup>A</sup>			
1660	1669 Mesh <sup>A</sup>			
1690	1699 Mesh <sup>A</sup>			
0340	0349 Mesh <sup>A</sup>			
0350	0359 Mesh <sup>A</sup>			
0370	0379 Mesh <sup>A</sup>			

A= With mounting screws B= With mounting Velcro

+ EZ-CLICK™ MOLLE PANEL

The first lid organiser of

its kind that can quickly be

released and swapped out

without tools. Engineered

to fit in the 1510 and 1560

Peli cases, the panel is compatible with user-

supplied MOLLE pouches

and Velcro<sup>™</sup> brand straps.

# + PICK N PLUCK™ FOAM

An easy, do-it-yourself system for the interior of the case. Layers of foam are pre-scored in 1,27 cm or 2,54 cm cubes. Simply lay your equipment on the foam, tape or chalk to mark the foam, and pluck away. Always allow at least 2,5 cm of foam between your equipment and the case wall.

The following cases ship with solid foam instead of Pick N Pluck<sup>™</sup> Foam: 1700, 1720, 1750





## + TREKPAK™ DIVIDERS\*

The TrekPak™ system uses pre-installed wall sections, divider panels, locking pins and an infallible cutting tool. Just lay your gear in the case, measure and cut the divider sections and lock them in place with the steel

\* Trekpak<sup>™</sup> is available for the following models: 1450, 1500. 1510, 1550, 1560, 1600, 1610, 1650,



Many Peli™ cases can be adapted for use with electronic interface panels by using a Panel Frame. Pre-drilled holes and stainless steel screws make fabricating a custom case a fast and accurate proposition.



Custom foam and extreme solutions

such as deck mount suspension systems will keep your delicate

items protected on the inside.

A polymer o-ring seals the panel so the base of the case remains watertight, even with the lid open.

The following cases are adaptable for use with panel frames: 1120, 1150, 1200, 1300, 1400, 1430, 1450, 1470, 1490, 1500, 1520, 1550 (search for the icon )



- O-ring Panel Frame
- Attachment Hardware



# + ELECTRONIC INSTALLATIONS



Peli™ Case allows customisation for electronics. The copolymer material can be machined, drilled and sanded smooth. This makes the Peli™ Case suitable for use with bulkhead connectors.

#### + PADDED DIVIDERS

An alternative to Peli<sup>™</sup> foam is our optional Padded Divider Sets. The compartments are connected with Velcro® so you can easily change the configuration according to your needs.

	PAD	DED DIVIDER OPTIONS	
CASE	LAYERS	CASE WITH DIVIDERS (CAT. NO.)	DIVIDER SET ONLY (CAT. NO.)
1450	1	1454	1455
1500	1	1504*	1505*
1510	1	1514*	1515*
1520	1	1524	1525
1550	1	1554*	1555*
1560	1	1564*	1565*
1600	1	1604	1605
1610	1	1614	1615
1620	2	1624	1625
1630	2	1634	1635
1640	2	1644	1645
1650	1	1654*	1655*
1660	2	1664	1665
1690	2	1694	1695
0340	2	0344	0345
0350	2	0354	0355
0370	2	0374	0375



\* These cases/sets come with new high-visibility yellow dividers. All others with standard black

#### HYBRID PROTECTION

TrekPak™ divider system or the protection of the manually customisable Pick N Pluck™ foam. Peli™ Hybrid protection features both. Only available for the Peli™ 1510 case as a standard offering.



## WE CUSTOMISE YOUR LOGO

Personalise your case with your company logo or have your name engraved on the nameplate. Logos can be applied in multiple colours as a Mylar® decal or as a vibrant fade-resistant, scratch-resistant hot-stamped ink.



CASE CONTENTS NOT INCLUDE CASE CONTENTS NOT INCLUDED



## **R20**

#### INTERNAL DIMS: 18 x 8.6 x 5 cm

• Rubber exo-skeleton

Multiple external attachment points

• Dual pivot latch

(7.07" x 3.39" x 1.95") EXTERNAL DIMS:

22.8 x 12.3 x 7.3 cm (8.96" x 4.83" x 2.88")

LID/BOTTOM DEPTH:

WEIGHT: 0.6 kg (1.26 lbs)



#### **R40**

brand straps

Rigid divider t

Cable routing hol

#### INTERNAL DIMS:

19.4 x 11.9 x 4.8 cm (7.63" x 4.70" x 1.90")

EXTERNAL DIMS: 25 x 15.5 x 7.3 cm (9.84" x 6.12" x 2.89")

LID/BOTTOM DEPTH: N/A

WEIGHT: 0.8 kg (1.68 lbs)




# P68 VATERPROOF, DEPTH OF 30 MINUTES

#### **R60**

#### INTERNAL DIMS: 22.6 x 13.6 x 7.5 cm (8.90" x 5.37" x 2.96")

EXTERNAL DIMS: 28.3 x 17.4 x 9.9 cm (11.14" x 6.86" x 3.88" LID/BOTTOM DEPTH:

WEIGHT:



## CASE CONTENTS NOT INCLUDED

#### M60

WEIGHT:

0.1 kg (0.33 lbs)

\*clear


#### INTERNAL DIMS: 1.1 x 6.5 x 10.4 cm

(0.43" x 2.56" x 4.10") EXTERNAL DIMS:

2 x 7.6 x 12.7 cm (0.80" x 3.00" x 5.00")

LID/BOTTOM DEPTH: N/A WEIGHT:

0.1 kg (0.33 lbs) \*clear



**G5 RF FIELD WALLET** 

#### INTERNAL DIMS: 1.1 x 6.5 x 10.4 cm

(0.43" x 2.56" x 4.10") EXTERNAL DIMS:

2 x 7.6 x 12.7 cm (0.80" x 3.00" x 5.00") LID/BOTTOM DEPTH:

CASE CONTENTS NOT INCLUDED

WEIGHT: 0.1 kg (0.33 lbs)



LID/BOTTOM DEPTH:

WEIGHT: 0.1 kg (0.33 lbs)

\*clear



# data theft and keeps cards safe.

#### **0915 CASE**

#### INTERNAL DIMS:

12.2 x 5.7 x 1.4 cm (4.79" x 2.25" x 0.55") EXTERNAL DIMS:

14.1 x 8.3 x 2.2 cm (5.55" x 3.27" x 0.85") LID/BOTTOM DEPTH:

WEIGHT:

0.1 kg (0.22 lbs) WITH LINER

Stores 12 SD cards, 6 mini SD cards and 6 micro SD cards (not included)



For the most up-to-date information, please visit www.peli.com or www.pelicatalogue.com PELI CASES CATALOGUE 7

#### 0965 CASE

INTERNAL DIMS: 12.2 x 5.7 x 1.4 cm (4.79" x 2.25" x 0.55")

**EXTERNAL DIMS:** 14.1 x 8.3 x 2.2 cm (5.55" x 3.27" x 0.85") LID/BOTTOM DEPTH:

0.1 kg (0.22 lbs)

WEIGHT:

Stores XQD and CFexpress cards (not included)



INTERNAL DIMS: 11.1 x 7.3 x 4.3 cm (4.37" x 2.87" x 1.68")

EXTERNAL DIMS: 14.9 x 10.3 x 5.4 cm (5.88" x 4.06" x 2.12")

LID/BOTTOM DEPTH: 1.8 cm / 2.4 cm (0.69" / 0.94")

WEIGHT: 0.19 kg (0.41 lbs.) WITH FOAM 0.18 kg (0.4 lbs) NO FOAM



#### **1015 MICRO CASE**

INTERNAL DIMS: 13.1 x 6.7 x 3.5 cm (5.14" x 2.64" x 1.37") **EXTERNAL DIMS:** 17 x 9.9 x 4.7 cm (6.68" x 3.88" x 1.86")

LID/BOTTOM DEPTH: 1.1 cm / 2.4 cm (0.43" / 0.94")

WEIGHT: 0.21 kg (0.46 lbs)



#### **1020 MICRO CASE**

INTERNAL DIMS: 13.5 x 9 x 4.3 cm (5.31" x 3.56" x 1.68") EXTERNAL DIMS:

17.3 x 12.1 x 5.4 cm (6.82" x 4.75" x 2.12")

LID/BOTTOM DEPTH: 1.8 cm / 2.4 cm (0.69" / 0.94")

0.25 kg (0.56 lbs) WITH FOAM 0.25 kg (0.55 lbs) NO FOAM



#### **1030 MICRO CASE**

INTERNAL DIMS: 16.2 x 6.7 x 5.2 cm (6.37" x 2.62" x 2.06")

EXTERNAL DIMS: 19.1 x 9.8 x 6.2 cm (7.5" x 3.87" x 2.43")

LID/BOTTOM DEPTH: 1.8 cm / 3.2 cm (0.69" / 1.25")

WEIGHT:

0.28 kg (0.61 lbs) WITH FOAM 0.27 kg (0.6 lbs) NO FOAM



#### **1040 MICRO CASE**

INTERNAL DIMS: 16.5 x 9.8 x 4.4 cm (6.5" x 3.87" x 1.75")

**EXTERNAL DIMS:** 19.1 x 12.9 x 5.4 cm (7.5" x 5.06" x 2.12")

LID/BOTTOM DEPTH: 1.8 cm / 2.4 cm (0.69" / 0.94")

WEIGHT:

0.32 kg (0.71 lbs) WITH FOAM 0.32 kg (0.7 lbs) NO FOAM



#### **1050 MICRO CASE**

INTERNAL DIMS: 16 x 9.3 x 7 cm (6.31" x 3.68" x 2.75") EXTERNAL DIMS: 20.3 x 12.9 x 7.9 cm (7.99" x 5.06" x 3.12")

LID/BOTTOM DEPTH: 1.8 cm / 4.9 cm (0.69" / 1.94")

WFTGHT-

0.38 kg (0.83 lbs) WITH FOAM 0.37 kg (0.81 lbs) NO FOAM



#### **1060 MICRO CASE**

INTERNAL DIMS: 21 x 10.8 x 5.7 cm (8.25" x 4.25" x 2.25") EXTERNAL DIMS:

25.1 x 14.2 x 6.7 cm (9.88" x 5.59" x 2.63") LID/BOTTOM DEPTH:

1.8 cm / 3.7 cm (0.69" / 1.44") WEIGHT:

0.47 kg (1.03 lbs) WITH FOAM 0.45 kg (1 lbs) NO FOAM

For the most up-to-date information, please visit www.peli.com or www.pelicatalogue.co





\*Other colours and configurations available upon minimum quantities. Check with your Customer Service representative for further details

CASE CONTENTS NOT INCLUDED

# **1120 CASE**

Pick N Pluck™ foam.

INTERNAL DIMS: 18.5 x 12.1 x 8.5 cm (7.29" x 4.78" x 3.33")

EXTERNAL DIMS: 21.4 x 17.2 x 9.8 cm (8.41" x 6.76" x 3.87")

LID/BOTTOM DEPTH: 1.3 cm / 6.5 cm (0.5" / 2.56") WEIGHT:

0.65 kg (1.43 lbs) WITH FOAM 0.61 kg (1.34 lbs) NO FOAM





SMALL CASES

Lightweight, but extremely strong; compact, ye

hand held GPS systems, and DSLR cameras. All

fully capable. Perfect for valuable gear like hand

tools and small to medium electronic components,

small cases are available empty or with pre-scored

#### 1150 CASE

INTERNAL DIMS: 21.1 x 14.7 x 9.5 cm (8.29" x 5.79" x 3.75") EXTERNAL DIMS:

24 x 19.8 x 10.9 cm (9.44" x 7.8" x 4.29")

LID/BOTTOM DEPTH: 1.9 cm / 7.3 cm (0.75" / 2.87") WEIGHT:

0.79 kg (1.75 lbs) WITH FOAM 0.73 kg (1.61 lbs) NO FOAM



**N**PELI

#### 1170 CASE

INTERNAL DIMS: 26.8 x 15.3 x 8 cm (10.54" x 6.04" x 3.16")

EXTERNAL DIMS: 29.6 x 21.2 x 9.6 cm (11.64" x 8.34" x 3.78")

LID/BOTTOM DEPTH: 2.7 cm / 5.3 cm (1.08"/ 2.08")

WEIGHT: 0.95 kg (2.1 lbs) WITH FOAM 0.89 kg (1.96 lbs) NO FOAM



# 1200 CASE

INTERNAL DIMS: 24 x 18.5 x 10.5 cm (9.31" x 7.13" x 4.12")

**EXTERNAL DIMS:** 27 x 24.5 x 12.4 cm (9.31" x 7.13" x 4.12")

LID/BOTTOM DEPTH: 3 cm / 7 cm (1.19" / 2.93")

WEIGHT: 1.3 kg (2.87 lbs) WITH FOAM 1.15 kg (2.65 lbs) NO FOAM



#### 1300 CASE

INTERNAL DIMS: 23.3 x 17.8 x 15.5 cm (9.17" x 7" x 6.12") EXTERNAL DIMS: 27 x 24.6 x 17.4 cm (10.62" x 9.68" x 6.87")

LID/BOTTOM DEPTH: 3 cm / 12.5 cm (1.18" / 4.93") WEIGHT:

1.6 kg (3.53 lbs) WITH FOAM 1.4 kg (3.09 lbs) NO FOAM

Adaptable for use with panel frame CASE CONTENTS NOT INCLUDED

# GERMANY

#### 1400 CASE INTERNAL DIMS: 30.1 x 22.8 x 13.1 cm

(11.87" x 8.97" x 5.15") EXTERNAL DIMS: 34.7 x 29.5 x 14.6 cm (13.68" x 11.61" x 5.75") LID/BOTTOM DEPTH: 3 cm / 10.2 cm (1.18" / 4")

WEIGHT: 2 kg (4.41 lbs) WITH FOAM 1.8 kg (3.97 lbs) NO FOAM



\*Other colours and configurations available upon minimum quantities. Check with your Customer Service representative for further details

For the most up-to-date information, please visit www.peli.com or www.pelicatalogue.com PELI CASES CATALOGUE 9



## **1075 HARDBACK™ CASE**

INTERNAL DIMS: 28.2 x 20.1 x 4.1 cm (11.11" x 7.92" x 1.63")

EXTERNAL DIMS: 31.4 x 24.8 x 5.4 cm (12.38" x 9.75" x 2.13")

LID/BOTTOM DEPTH: 2.1 cm (0.81")

WEIGHT: 0.7 kg (1.54 lbs) WITH FOAM 0.6 kg (1.41 lbs) NO FOAM



#### 1085 HARDBACK™ CASE

INTERNAL DIMS: 36.3 x 26.3 x 5 cm (14.29" x 10.37" x 1.97")

EXTERNAL DIMS: 39.7 x 31.5 x 6.4 cm (15.64" x 12.41" x 2.5")

LID/BOTTOM DEPTH: 2.5 cm (0.99")

WEIGHT: 1.4 kg (3.1 lbs) WITH FOAM 1.2 kg (2.65 lbs) NO FOAM





#### 1095 HARDBACK™ CASE

INTERNAL DIMS: 40.1 x 28.3 x 5.2 cm (15.78" x 11.16" x 2.06") EXTERNAL DIMS: 43.6 x 33.6 x 6.6 cm (17.18" x 13.24" x 2.6") LID/BOTTOM DEPTH:

2.6 cm (1.03") WEIGHT: 1.6 kg (3.49 lbs) WITH FOAM

1.4 kg (3.05 lbs) NO FOAM





#### 1095CC HARDBACK™ CASE

INTERNAL DIMS: 40.1 x 28.3 x 5.2 cm (15.78" x 11.16" x 2.06") EXTERNAL DIMS: 43.6 x 33.6 x 6.6 cm (17.18" x 13.24" x 2.6") LID/BOTTOM DEPTH: 2.6 cm (1.03") WEIGHT: 1.5 kg (3.29 lbs) WITH FOAM



CASE CONTENTS NOT INCLUDED

#### 1470 CASE

INTERNAL DIMS:

39.9 x 27.2 x 9.8 cm (15.7" x 10.7" x 3.87")

EXTERNAL DIMS: 42.9 x 33.6 x 11.4 cm

(16.88" x 13.23" x 4.47") LID/BOTTOM DEPTH: 3.7 cm / 6.1 cm (1.47" / 2.4")

2.5 kg (5.51 lbs) WITH FOAM 1.94 kg (4.28 lbs) NO FOAM

1490 CASE

INTERNAL DIMS:

EXTERNAL DIMS:

45.1 x 28.9 x 10.5 cm (17.75" x 11.37" x 4.12")

50.5 x 35.4 x 11.9 cm

(19.87" x 13.93" x 4.68") LID/BOTTOM DEPTH:

3.8 cm / 6.7 cm (1.5" / 2.62")

2.95 kg (6.5 lbs) WITH FOAM 2.48 kg (5.47 lbs) NO FOAM






#### 1490CC1 CASE

INTERNAL DIMS: 45.1 x 28.9 x 10.5 cm (17.75" x 11.37" x 4.12") EXTERNAL DIMS:

50.5 x 35.4 x 11.9 cm (19.87" x 13.93" x 4.68") LID/BOTTOM DEPTH:

3.8 cm / 6.7 cm (1.5" / 2.62") WEIGHT: 2.95 kg (6.5 lbs) WITH FOAM

2.48 kg (5.47 lbs) NO FOAM



#### 1495 CASE

INTERNAL DIMS: 47.9 x 33.3 x 9.7 cm (18.87" x 13.12" x 3.81")

EXTERNAL DIMS: 54.9 x 43.8 x 12.4 cm (21.62" x 17.25" x 4.87")

LID/BOTTOM DEPTH: 2.8 cm / 6.8 cm (1.12" / 2.68") WEIGHT:

3.8 kg (8.37 lbs) WITH FOAM 3.28 kg (7.23 lbs) NO FOAM



## **1495CC1 CASE**

INTERNAL DIMS: 47.9 x 33.3 x 9.7 cm (18.87" x 13.12" x 3.81")

EXTERNAL DIMS: 54.9 x 43.8 x 12.4 cm (21.62" x 17.25" x 4.87")

LID/BOTTOM DEPTH: 2.8 cm / 6.8 cm (1.12" / 2.68") WEIGHT: 5.03 kg (11.1 lbs)



INTERNAL DIMS: 34.4 x 14.6 x 29.7 cm (13.56" x 5.76" x 11.7")

EXTERNAL DIMS: 41.7 x 22.1 x 33.4 cm (16.4" x 8.71" x 13.15")

LID/BOTTOM DEPTH: 5.1 cm / 24.6 cm (2" / 9.7") WETGHT:

2.95 kg (6.5 lbs) WITH FOAM 2.54 kg (5.6 lbs) NO FOAM





43.4 x 19.1 x 40.6 cm (17.1" x 7.5" x 16") EXTERNAL DIMS:

INTERNAL DIMS:

50 x 30.5 x 45.7 cm (19.7" x 12" x 18")

LID/BOTTOM DEPTH: 5.1 cm / 35.6 cm (2" / 14") WETGHT:

7.48 kg (16.5 lbs) WITH FOAM 6.58 kg (14.5 lbs) NO FOAM



Adaptable for use with panel frame CASE CONTENTS NOT INCLUDED

\*Other colours and configurations available upon minimum quantities. Check with your Customer Service representative for further details

Adaptable for use with panel frame

INTERNAL DIMS:

37.4 x 26 x 15.4 cm

(14.72" x 10.22" x 6.08") EXTERNAL DIMS:

40.9 x 33.1 x 17.5 cm (16.1" x 13.03" x 6.88")

LID/BOTTOM DEPTH: 4.4 cm / 11.1 cm (1.75" / 4.37")

1460 CASE

INTERNAL DIMS:

47.1 x 25.2 x 27.7cm

53 x 32.3 x 32.4 cm

(18.54" x 9.92" x 10.92") **EXTERNAL DIMS:** 

(20.85" x 12.73" x 12.75")

12.5 cm / 15.3 cm (4.91" / 6.01")

LID/BOTTOM DEPTH:

2.9 kg (6.39 lbs) WITH FOAM 2.5 kg (5.51 lbs) NO FOAM













For the most up-to-date information, please visit www.peli.com or w

\*Other colours and configurations available upon minimum quantities. Check with your Customer Service representative for further details. \*\* This case is only available upon minimum quantities in both colours



#### 1510 CASE Similarly sized Peli Storm Case: iM2500 INTERNAL DIMS: 51 x 28.5 x 19.3 cm (19.75" x 11" x 7.6") **EXTERNAL DIMS:** 55 x 36 x 22.9 cm (22" x 13.81" x 9") LID/BOTTOM DEPTH: 4 cm / 15 cm (1.79" / 5.79") 6.17 kg (13.6 lbs) WITH FOAM 5.59 kg (11.99 lbs) NO FOAM \*

INTERNAL DIMS:

(19.75" x 11" x 7.6")

EXTERNAL DIMS:

(22" x 13.81" x 9")

WEIGHT:

55.9 x 35.1 x 22.9 cm

LID/BOTTOM DEPTH:

6.77 kg (14.94 lbs)

**1510 SC CASE** 

INTERNAL DIMS:

(19.75" x 11" x 7.6")

EXTERNAL DIMS:

(22" x 13.81" x 9")

WEIGHT:

55.9 x 35.1 x 22.9 cm

LID/BOTTOM DEPTH:

4.5 cm / 14.7 cm (1.79" / 5.79")

6.2 kg (13.6 lbs) WITH FOAM

Adaptable for use with panel frame

CASE CONTENTS NOT INCLUDED

5.4 kg (11.99 lbs) NO FOAM

50.2 x 27.9 x 19.3 cm

50.1 x 27.9 x 19.3 cm












LID/BOTTOM DEPTH: 4.5 cm / 14.7 cm (1.79" / 5.79") WEIGHT: 6.2 kg (13.6 lbs) WITH FOAM 5.4 kg (11.99 lbs) NO FOAM














\*Other colours and configurations available upon minimum quantities. Check with your Customer Service representative for further details This case is only available upon minimum quantities

53 x 32.3 x 32.4 cm

8.26 kg (18.2 lbs)

WETGHT:

(20.85" x 12.73" x 12.75")

LID/BOTTOM DEPTH:

WITH TRAY ASSEMBLY
















#### 1560 CASE

INTERNAL DIMS: 51 x 39 x 22.9 cm (19.92" x 14.98" x 9")

**EXTERNAL DIMS:** 55 x 45.5 x 26.5 cm (22.07" x 17.92" x 10.42")

LID/BOTTOM DEPTH: 5 cm / 18 cm (2" / 7")

WEIGHT:

9.07 kg (20 lbs) WITH FOAM 6.84 kg (17 lbs) NO FOAM





#### **1560M CASE**

INTERNAL DIMS: 50.6 x 38 x 22.9 cm (19.92" x 14.98" x 9")

EXTERNAL DIMS: 60.4 x 46.6 x 30.7 cm (23.78" x 18.33" x 12.08")

LID/BOTTOM DEPTH: 5.1 cm / 17.8 cm (2" / 7")

WEIGHT: 11 KG (24.3 LBS) WITH FOAM 9.7 KG (21.3 LBS) NO FOAM



INTERNAL DIMS: 54.3 x 41.4 x 31.9 cm (21.37" x 16.31" x 12.56")

EXTERNAL DIMS: 63 x 49.2 x 35.2 cm (24.81" x 19.37" x 13.87")

LID/BOTTOM DEPTH: 5.2 cm / 26.7 cm (2.06" / 10.5")

11.8 kg (26.01 lbs) WITH FOAM 11.1 kg (24.47 lbs) NO FOAM



## **1620M CASE**

INTERNAL DIMS: 54.6 x 41.7 x 31.9 cm (21.48" x 16.42" x 12.54")

EXTERNAL DIMS: 66.5 x 58.4 x 39.6 cm

(26.2" x 23" x 15.61") LID/BOTTOM DEPTH: 5.1 cm / 26.7 cm

(2.01" / 10.53") WEIGHT:

14.3 kg (31.42 lbs) WITH FOAM 12.7 kg (28 lbs) NO FOAM



#### 1560LOC CASE

INTERNAL DIMS: 50.6 x 38 x 22.9 cm (19.92" x 14.98" x 9")

EXTERNAL DIMS: 56.1 x 45.5 x 26.5 cm (22.07" x 17.92" x 10.42")

LID/BOTTOM DEPTH: 5.1 cm / 17.8 cm (2" / 7")

WETGHT:

8.2 kg (18.18 lbs) WITH FOAM 7.7 kg (17 lbs) NO FOAM



#### 1560SC CASE

INTERNAL DIMS: 50.6 x 38 x 22.9 cm (19.92" x 14.98" x 9")

EXTERNAL DIMS: 56.1 x 45.5 x 26.5 cm (22.07" x 17.92" x 10.42")

LID/BOTTOM DEPTH: 5.1 cm / 17.8 cm (2" / 7") WETGHT:

8.2 kg (18.18 lbs) WITH FOAM 7.7 kg (17 lbs) NO FOAM



CASE CONTENTS NOT INCLUDED

#### **INTACT AFTER MASSIVE EXPLOSION**

My team and I were first responders to a terrorist attack on a hotel in Islamabad, Pakistan. As part of our recovery effort at the blast site, we 'repatriated' one of our armored vehicles. Inside the vehicle, which was in the immediate impact zone of the SVBIED, we discovered an unscathed 'Model 1640 Peli Transport Case™.' The case stood up against a massive explosion and flying shrapnel. Seeing how well this product withstood this type of abuse, I can say that you have found yourself several new lifetime customers!

**US Federal Agent** 

CASE CONTENTS NOT INCLUDED

\*Other colours and configurations available upon minimum quantities. Check with your Customer Service representative for further details

\*Other colours and configurations available upon minimum quantities. Check with your Customer Service representative for further details.

14 PELI CASES CATALOGUE

+ STORIES

#### Tim Cothren, wildlife photographer



1650 CASE Similarly sized Peli Storm Case: iM2950



WEIGHT: 12.73 kg (28.06 lbs) WITH FOAM 10.9 kg (24.03 lbs) NO FOAM

**1670 CASE** 

**INTERNAL DIMS:** 

**EXTERNAL DIMS:** 

71.4 x 41.9 x 23.3 cm

(28.1" x 16.49" x 9.19")

78.8 x 49.3 x 28.4 cm

LID/BOTTOM DEPTH:

(31.04" x 19.39" x 11.17")

4.6 cm / 18.8 cm (1.8" / 7.39")

11.8 kg (26 lbs) WITH FOAM

10.4 kg (23 lbs) NO FOAM



#### 1630 CASE

INTERNAL DIMS: 70.4 x 53.3 x 39.4 cm (27.7" x 20.98" x 15.5")

EXTERNAL DIMS:

79.5 x 61.5 x 44.4 cm (31.28" x 24.21" x 17.48")

LID/BOTTOM DEPTH: 8.3 cm / 30.8 cm (3.25" / 12.14")

16.33 kg (36 lbs) WITH FOAM 14.06 kg (31 lbs) NO FOAM



#### **1640 CASE**

INTERNAL DIMS: 60.2 x 61 x 35.3 cm (23.7" x 24" x 13.9") EXTERNAL DIMS:

69.1 x 69.9 x 41.4 cm (27.2" x 27.5" x 16.3") LID/BOTTOM DEPTH:

5.1 cm / 30.2 cm (2" / 11.9") WEIGHT:

17.24 kg (38 lbs) WITH FOAM 15.42 kg (34 lbs) NO FOAM

MADE IN

GERMANY



MADE IN

GERMANY

#### 1660 CASE


INTERNAL DIMS: 71.6 x 50.2 x 44.8 cm (28.18" x 19.75" x 17.62")

EXTERNAL DIMS: 80 x 58.1 x 48.3 cm (31.5" x 22.87" x 19")

LID/BOTTOM DEPTH: 8.9 cm / 35.9 cm (3.5" / 14.12")

WEIGHT:

19.1 kg (42.11 lbs) WITH FOAM 15.5 kg (34.17 lbs) NO FOAM



INTERNAL DIMS: 76.5 x 63.8 x 39 cm (30.13" x 25.13" x 15.36")

EXTERNAL DIMS: 84.9 x 72.1 x 44.8 cm (33.43" x 28.4" x 17.65") LID/BOTTOM DEPTH:

7.3 cm / 30.8 cm (2.86" / 12.14") WETGHT: 19.5 kg (43 lbs) WITH FOAM

15.42 kg (34 lbs) NO FOAM

For the most up-to-date information, please visit www.peli.com or www.pelicatalogue.co



#### 1730 CASE

LID/BOTTOM DEPTH:

WEIGHT: 17.24 kg (38 lbs) WITH FOAM



INTERNAL DIMS: 86.4 x 61 x 31.8 cm (34" x 24" x 12.5")

EXTERNAL DIMS: 95.3 x 68.9 x 36.5 cm (37.5" x 27.13" x 14.37")

6.4 cm / 25.4 cm (2.5" / 1")

13.61 kg (30 lbs) NO FOAM



#### 1780 CASE

INTERNAL DIMS: 104.4 x 54.7 x 37.8 cm (41.12" x 21.54" x 14.88")

**EXTERNAL DIMS:** 114 x 64.3 x 41.9 cm (44.9" x 25.32" x 16.5")

LID/BOTTOM DEPTH: 19.3 cm / 18.5 cm (7.58" / 7.3") WEIGHT:

22.2 kg (49 lbs) WITH FOAM 17.4 kg (38.4 lbs) NO FOAM



#### **0340 CASE**

INTERNAL DIMS: 45.7 x 45.7 x 45.7 cm (18" x 18" x 18")

EXTERNAL DIMS: 52.1 x 52.1 x 48.9 cm

(20.5" x 20.5" x 19.25") LID/BOTTOM DEPTH:

11.4 cm / 34.3 cm (4.5" / 13.5") WEIGHT:

13.5 kg (29.76 lbs) WITH FOAM 10.89 kg (24 lbs) NO FOAM



#### **0350 CASE**

INTERNAL DIMS: 50.8 x 50.8 x 50.8 cm (2" x 2" x 2")

**EXTERNAL DIMS:** 57.2 x 57 x 54 cm (22.5" x 22.43" x 21.25")

LID/BOTTOM DEPTH: 12.7 cm / 38.1 cm (5" / 15")

WEIGHT: 14.52 kg (32.01 lbs) WITH FOAM 11.79 kg (25.99 lbs) NO FOAM



#### **0370 CASE**

INTERNAL DIMS: 61 x 61 x 61 cm (24" x 24" x 24")

EXTERNAL DIMS: 67.3 x 67.3 x 64.1 cm (26.5" x 26.5" x 25.25")

LID/BOTTOM DEPTH: 12.7 cm / 48.3 cm (5" / 19")

WEIGHT:

18.6 kg (41 lbs) WITH FOAM 14.5 kg (31.97 lbs) NO FOAM



# **0450 CASE**

INTERNAL DIMS: Varies by drawer configuration

EXTERNAL DIMS: 60.8 x 37.5 x 45.6 cm (23.95" x 14.75" x 17.95")

LID/BOTTOM DEPTH: N/A

WEIGHT: 21.95 kg (48.4 lbs)



#### **0500 CASE**

INTERNAL DIMS: 88.8 x 46.9 x 64.1 cm (34.95" x 18.45" x 25.25")

EXTERNAL DIMS: 101.5 x 59.6 x 72.8 cm (39.95" x 23.45" x 28.65")

LID/BOTTOM DEPTH: 5.7 cm / 58.4 cm (2.25" / 23")

WEIGHT: 26.58 kg (58.6 lbs) WITH FOAM

22.68 kg (50 lbs) NO FOAM



#### **0550 CASE**

INTERNAL DIMS: 120.8 x 61.1 x 44.9 cm (47.57" x 24.07" x 17.68" EXTERNAL DIMS:

129.7 x 70 x 57.9 cm (51.05" x 27.54" x 22.79") LID/BOTTOM DEPTH: 8.1 cm / 36.8 cm

(3.19" / 14.49") WEIGHT: 43.09 kg (95 lbs) WITH FOAM

35.92 kg (79.2 lbs) NO FOAM



\*Other colours and configurations available upon minimum quantities. Check with your Customer Service representative for further details.

CASE CONTENTS NOT INCLUDED CASE CONTENTS NOT INCLUDED

\*Other colours and configurations available upon minimum quantities. Check with your Customer Service representative for further details

WETGHT:





For the most up-to-date information, please visit www.peli.com or www.pelicatalogue.com

1700 CASE Similarly sized Peli Storm Case: iM3100

INTERNAL DIMS: 91 x 35.3 x 13.3 cm (35.75" x 13.5" x 5.25") EXTERNAL DIMS:

96 x 45.5 x 15.5 cm (38.12" x 16" x 6.12")

LID/BOTTOM DEPTH: 4.5 cm / 8.6 cm (1.75" / 3.5")

7.7 kg (16.98 lbs) WITH FOAM 6.64 kg (16.09 lbs) NO FOAM

1720 CASE Similarly sized Peli Storm Case: iM3200

INTERNAL DIMS:

MADE IN

GERMANY

106.2 x 34.5 x 13.5 cm (41.80" x 13.58" x 5.33") EXTERNAL DIMS:

113 x 40.8 x 15.9 cm (44.48" x 16.07" x 6.25") LID/BOTTOM DEPTH:

4.4 cm / 8.9 cm (1.75" / 3.5")

10.5 kg (23.10 lbs) WITH FOAM 8.3 kg (18.25 lbs) NO FOAM



#### 1740 CASE

INTERNAL DIMS: 104.1 x 32.8 x 30.8 cm (40.98" x 12.92" x 12.13")

EXTERNAL DIMS: 112,2 x 40,9 x 35,6 cm (44.16" x 16.09" x 14")

LID/BOTTOM DEPTH: 6.5 cm / 24.3 cm (2.56" / 9.57"

WEIGHT: 12.25 kg (27 lbs) WITH FOAM 9.98 kg (22 lbs) NO FOAM



1750 CASE Similarly sized Peli Storm Case: iM3300

INTERNAL DIMS: 128 x 33.9 x 13.5 cm (50.38" x 13.33" x 5.33") **EXTERNAL DIMS:** 142.4 x 40.8 x 15.6 cm (56.06" x 16.05" x 6.13"

LID/BOTTOM DEPTH: 4.4 cm / 8.9 cm

(1.75" / 3.5") WEIGHT:

12.1 kg (26.70 lbs) WITH FOAM 9.5 kg (21.00 lbs) NO FOAM

#### INTERNAL DIMS:

1770 CASE

138.6 x 39.6 x 21.9 cm (54.58" x 15.58" x 8.63")

EXTERNAL DIMS: 145.8 x 46.9 x 28.5 cm (57.42" x 18.48" x 11.23")

LID/BOTTOM DEPTH: 4.8 cm / 17.1 cm (1.88" / 6.75")

WEIGHT: 18.8 kg (41.49 lbs) WITH FOAM 16.3 kg (36.01 lbs) NO FOAM

## 1780 CASE

INTERNAL DIMS:

104.4 x 54.7 x 37.8 cm (41.12" x 21.54" x 14.88")

EXTERNAL DIMS: 114 x 64.3 x 41.9 cm (44.9" x 25.32" x 16.5") LID/BOTTOM DEPTH:

19.3 cm / 18.5 cm (7.58" / 7.3")

WEIGHT: 22.2 kg (49 lbs) WITH FOAM 17.4 kg (38.4 lbs) NO FOAM



#### STUCK IN THE MUD?

SURVIVAL
+ STORIES

During our trip across the Saharan Desert on our Africa Twin motorcycles, we went through a lot, traveling through sand, mud and water as well as over rock and asphalt. At one point, we attempted to cross a massive pool of mud that was blocking the road. The thinking was that going through at full speed would allow us to fly across the muddy area to the other side unscathed. Needless to say, that didn't happen. The bike was stuck for hours, but ultimately, we got it out. Later, we opened our Peli cases to find that the drone, sleeping bag, spare motor parts, food and clothes inside the cases remained perfectly dry and protected. There was never a doubt in our minds.

Honda Revival Team @hondarevivalteam

\*Other colours and configurations available upon minimum quantities. Check with your Customer Service representative for further details

18 PELI CASES CATALOGUE



# PELI CASE SPECIFICATIONS AND FEATURES

	<u> </u>	AGE OF E		IONOA	ND FEAT	JKLO					NTERI	$DIVID_{E}$	SED	ALISED TE NISER		
CAT. N	10.	INTERIOR DIMENSIONS (cm)	EXTERIOR DIMENSIONS (cm)	LID DEPTH	BOTTOM DEPTH	WEIGHT WITH FOAM	WEIGHT WITHOUT FOAM	BUOYANCY MAXIMUM	TEMPERATURE RANGE (Min/Max)	CERTIFICATES	HYBRID 1	PADDED!	HANDLES PANEL FR	PERSON NAMEPLA LID ORG	COLOURS	CAT
R	20	18 x 8.6 x 5	22.8 x 12.3 x 7.3	N/A	N/A	N/A	0.6 kg	0.7 kg	-23 / 93 ° C	IP68						R20
R	40	19.4 x 11.9 x 4.8	25 x 15.5 x 7.3	N/A	N/A	N/A	0.8 kg	1.1 kg	-23 / 93º C	IP68						R40
R	60	22.6 x 13.6 x 7.5	28.3 x 17.4 x 9.9	N/A	N/A	N/A	1.1 kg	2.2 kg	-23 / 93º C	IP68						R60
	140	25.2 x 9.7 x 5.3	17.3 x 12.7 x 6.6	2 cm	3.6 cm	N/A	0.3 kg	N/A	-23 / 93º C	IP67					■	M40
М	150	18.5 x 10.9 x 6.1	20.6 x 14 x 7.4	2 cm	3.6 cm	N/A	0.4 kg	N/A	-23 / 93º C	IP67			$\Box$		*clear	M50
М	160	21.6 x 10.9 x 6.9	23.6 x 15.2 x 8.1	2 cm	3.6 cm	N/A	0.5 kg	N/A	-23 / 93º C	IP67					■	M60
	F Field	1.1 x 6.5 x 10.4	2 x 7.6 x 12.7	N/A	N/A	N/A	Ø.15 kg	N/A	N/A	IP67			$\Box$			G5 RF Fie
09	915 965	12.2 x 5.7 x 1.4	14.1 x 8.3 x 2.2	N/A	N/A	0.1 kg	N/A	N/A	N/A	-						0915 0965
	010	11.1 x 7.3 x 4.3	14.9 x 10.3 x 5.4	1.8 cm	2.4 cm	0.19 kg	Ø.18 kg	0.23 kg	-23 / 93° C	IP67			$\top$		■ □*	1010
16	015	13.1 x 6.7 x 3.5	17 x 9.9 x 4.7	1.1 cm	2.4 cm	N/A	0.21 kg	0.54 kg	N/A	IP67					■*	1015
10	020	13.5 x 9 x 4.3	17.3 x 12.1 x 5.4	1.8 cm	2.4 cm	0.25 kg	0.25 kg	0.34 kg	-23 / 93° C	IP67					■-	1020
	030	16.2 x 6.7 x 5.2	19.1 x 9.8 x 6.2	1.8 cm	3.2 cm	0.28 kg	0.27 kg	0.45 kg	-23 / 93° C	IP67					■ _*	1030
10	040	16.5 x 9.8 x 4.4	19.1 x 12.9 x 5.4	1.8 cm	2.4 cm	0.32 kg	0.32 kg	0.57 kg	-23 / 93° C	IP67			$\top$		■-	1040
10	<b>050</b>	16 x 9.3 x 7	20.3 x 12.9 x 7.9	1.8 cm	4.9 cm	0.38 kg	0.37 kg	0.79 kg	-23 / 93° C	IP67			+		■ _*	1050
	060	21 x 10.8 x 5.7	25.1 x 14.2 x 6.7	1.8 cm	3.7 cm	0.47 kg	0.45 kg	1.13 kg	-23 / 93° C	IP67			+	+		1060
	120	18.5 x 12.1 x 8.5	21.4 x 17.2 x 9.8	1.3 cm	6.5 cm	0.65 kg	0.61 kg	2.27 kg	-40 / 99° C	IP67 • DEF STAN 81-41/STANAG 4280			0			1120
	150	21.1 x 14.7 x 9.5	24 x 19.8 x 10.9	1.9 cm	7.3 cm	0.79 kg	0.73 kg	3.63 kg	-40 / 99° C	IP67 • DEF STAN 81-41/STANAG 4280			0		<b>■</b> □*	1150
	170	26.8 x 15.3 x 8	29.6 x 21.2 x 9.6	2.7 cm	5.3 cm	0.95 kg	0.89 kg	3.29 kg	-40 / 99° C	IP67			+			1170
	200	24 x 18.5 x 10.5	27 x 24.5 x 12.4	3 cm	7 cm	1.3 kg	1.15 kg	5.45 kg	-40 / 99° C	IP67 • DEF STAN 81-41/STANAG 4280			0		<b>-</b>	1200
	300	23.3 x 17.8 x 15.5	27 x 24.6 x 17.4	3 cm	12.5 cm	1.6 kg	1.13 kg	5.6 kg	-40 / 99° C	IP67 • DEF STAN 81-41/STANAG 4280			0			1300
	400	30.1 x 22.8 x 13.1	34.7 x 29.5 x 14.6	3 cm	10.2 cm	2 kg	1.4 kg	9.1 kg	-40 / 99° C	IP67 • MIL C-4150J • DEF STAN 81-41/STANAG 4280 • ATA 300			0			1400
	075	28.2 x 20.1 x 4.1	31.4 x 24.8 x 5.4	2.1 cm	2.1 cm	0.7 kg		7.1 kg	-23 / 49° C	TPO7 - FILL C-41363 - DEF STAIN 61-41/STAINAG 4266 - ATA 366			+++			1075
							0.6 kg						++		-	
	085	36.3 x 26.3 x 5	39.7 x 31.5 x 6.4	2.5 cm	2.5 cm	1.4 kg	1.2 kg	N/A	-23 / 49° C				++		_	1085
	095	40.1 x 28.3 x 5.2	43.6 x 33.6 x 6.6	2.6 cm	2.6 cm	1.6 kg	1.4 kg	N/A	-23 / 49° C				++			1095
	95CC	40.1 x 28.3 x 5.2	43.6 x 33.6 x 6.6	2.6 cm	2.6 cm	1.5 kg	N/A	N/A	-23 / 49° C						<b>-</b>	1095C
	470	39.9 x 27.2 x 9.8	42.9 x 33.6 x 11.4	3.7 cm	6.1 cm	2.5 kg	1.94 kg	11.3 kg	-40 / 99° C	MIL C-4150J			0		*	1470
14	490	45.1 x 28.9 x 10.5	50.5 x 35.4 x 11.9	3.8 cm	6.7 cm	2.95 kg	2.48 kg	18.6 kg	-40 / 99° C	DEF STAN 81-41/STANAG 4280			0			1490
149	ØCC1	45.1 x 28.9 x 10.5	50.5 x 35.4 x 11.9	3.8 cm	6.7 cm	2.9 kg	2.5 kg	18.6 kg	-40 / 99° C	DEF STAN 81-41/STANAG 4280			0			1490CC
14	495	47.9 x 33.3 x 9.7	54.9 x 43.8 x 12.4	2.8 cm	6.8 cm	3.8 kg	3.28 kg	20.5 kg	-40 / 99° C	IP67 • DEF STAN 81-41/STANAG 4280		S	$\perp \perp$	0	•	1495
149	5CC1	47.9 x 33.3 x 9.7	54.9 x 43.8 x 12.4	2.8 cm	6.8 cm	5 kg	N/A	20.5 kg	-40 / 99° C	IP67 • DEF STAN 81-41/STANAG 4280		S		0 S	■*	1495CC
14	430	34.4 x 14.6 x 29.7	41.7 x 22.1 x 33.4	5.1 cm	24.6 cm	2.95 kg	2.54 kg	26.8 kg	-40 / 99° C	IP67 • DEF STAN 81-41/STANAG 4280		0 S	0	0 0	<b>=</b> *	1430
14	440	43.4 x 19.1 x 40.6	50 x 30.5 x 45.7	5.1 cm	35.6 cm	7.48 kg	6.58 kg	43.2 kg	-40 / 99° C	IP67 • DEF STAN 81-41/STANAG 4280		0 S	Ш	0 0 :	S <b>■</b> *	1440
14	450	37.4 x 26 x 15.4	40.9 x 33.1 x 17.5	4.4 cm	11.1 cm	2.9 kg	2.5 kg	13.61 kg	-40 / 99° C	IP67 • MIL C-4150J • DEF STAN 81-41/STANAG 4280		o s	0	0		1450
14	460	47.1 x 25.2 x 27.7	53 x 32.3 x 32.4	12.5 cm	15.3 cm	5.66 kg	3.97 kg	37.19 kg	-40 / 99° C	IP67		s			<b>=</b> *	1460
15	500	42.8 x 28.6 x 15.5	47.1 x 35.7 x 17.5	4.6 cm	10.9 cm	3.2 kg	2.9 kg	22.68 kg	-40 / 99° C	IP67 • MIL C-4150J • DEF STAN 81-41/STANAG 4280 • ATA 300		0 S	6 0	0 0		1500
15	510	51 x 28.5 x 19.3	55 x 36 x 22.9	4 cm	15 cm	6.17 kg <sup>A</sup>	5.59 kg	29.1 kg	-40 / 99° C	IP67 • DEF STAN 81-41/STANAG 4280	0 0	0 s		0 0	S •••	1510
15:	10M	50.2 x 27.9 x 19.3	59.8 x 36.5 x 27	4.5 cm	14.7 cm	8.1 kg	7.39 kg	N/A	-40 / 99° C	IP57		o s	,	0 0 :	s <b>=</b>	1510M
15	520	44.9 x 31.8 x 17.1	49.9 x 39.3 x 19.1	4.5 cm	12.5 cm	4.24 kg	3.76 kg	28.6 kg	-40 / 99° C	IP67 • MIL C-4150J • DEF STAN 81-41/STANAG 4280		0 s	0	0 0		1520
15	550	47.3 x 36 x 19.6	52.5 x 43.5 x 21.6	4.4 cm	14.9 cm	5.4 kg	4.8 kg	31.7 kg	-40 / 99° C	IP67 • MIL C-4150J • DEF STAN 81-41/STANAG 4280 • ATA 300	0	0 S				1550

<sup>A</sup>Weight with Hybrid interior: 6.77 kg (14.94 lbs)

<sup>\*</sup> Other colours and configurations available upon minimum quantities. Check with your Customer Service representative for further details.

# PELI CASE SPECIFICATIONS AND FEATURES

1680	S ■ 1610M S ■* 1620 S ■ 1620M S ■ * 1630
1566M   50.6 x 38 x 22.9   60.8 x 46.6 x 30.7   51.cm   17.8 cm   11.8 q   9.66 kg   N/A   -40/99°C   IP67 *MIL C-1150 * DEF STAN B1-41/STANAG 4280 * ATA 300   0   0   0   0   0   0   0   0   0	S
1600	Image: square of the color of the colo
1610 551 x 42 2 x 268 62.8 x 497 x 30.3 5.2 cm 21.6 cm 10.2 kg 9.07 kg 54.4 kg -40/99°C IP67 * DEF STAN 81-41/STANAG 4280 0 0 0 S 0 0 0 1610M 55.3 x 42.4 x 27 66.5 x 58.4 x 34.7 5.2 cm 21.8 cm 13.2 kg 11.93 kg N/A -40/99°C IP57 * MIL C-4150.3 DEF STAN 81-41/STANAG 4280 0 0 S 0 0 0 1620M 54.3 x 41.4 x 31.9 63 x 492 x 35.2 5.2 cm 26.7 cm 11.8 kg 11.1 kg 68 kg -40/99°C IP67 * MIL C-4150.3 DEF STAN 81-41/STANAG 4280 0 0 S 0 0 0 1620M 54.4 x 13.9 66.5 x 58.4 x 39.6 5.1 cm 26.7 cm 14.3 kg 12.7 kg N/A -40/99°C IP67 * MIL C-4150.3 DEF STAN 81-41/STANAG 4280 0 0 S 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	S ■* 1610 S ■ 1610M S ■ 1620 S ■ 1620M S ■ 1630
1610M 55.3 x 42.4 x 27 66.5 x 58.4 x 34.7 5.2 cm 21.8 cm 13.2 kg 11.93 kg N/A -40/9° C IP57 MIL C-4150.3 - DEF STAN 81-41/STANAG 4280 0 0 S 0 0 D 1620 54.3 x 41.4 x 31.9 63 x 49.2 x 35.2 5.2 cm 26.7 cm 11.8 kg 11.1 kg 68 kg -40/9° C IP67 • MIL C-4150.3 - DEF STAN 81-41/STANAG 4280 0 0 S 0 0 D 1620 M 54.5 x 41.7 x 31.9 65.5 x 84.2 x 39.6 5.1 cm 26.7 cm 14.3 kg 12.7 kg N/A -40/9° C IP67 • MIL C-4150.3 - DEF STAN 81-41/STANAG 4280 • D 0 S 0 D 0 D 0 D 0 D 0 D 0 D 0 D 0 D 0	S ■ 1610M S ■* 1620 S ■ 1620M S ■ * 1630
1620 54.3 x.41.4 x.31.9 63 x.49.2 x.35.2 5.2 cm 26.7 cm 11.8 kg 11.1 kg 68 kg -40/9° C 1P67 *MIL C-41503 *DEF STAN 81-41/STANAG 4280 0 0 S 0 0 0 1620M 54.6 x.41.7 x.31.9 66.5 x.58.4 x.39.6 5.1 cm 26.7 cm 14.3 kg 12.7 kg N/A -40/9° C 1P67 *DEF STAN 81-41/STANAG 4280 0 0 S 0 0 0 1630 70.4 x.53.3 x.39.4 79.5 x.61.5 x.44.4 8.3 cm 30.8 cm 16.33 kg 14.06 kg 159 kg -40/9° C 1P67 *DEF STAN 81-41/STANAG 4280 0 0 0 0 0 0 1640 60.2 x.61 x.35.3 69.1 x.69.7 x.41.4 5.1 cm 30.2 cm 17.24 kg 15.42 kg 16.6 kg -40/9° C 1P67 *DEF STAN 81-41/STANAG 4280 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	S ■ 1620 S ■ 1620M S ■ 1630
1620M 54.6 x 41.7 x 31.9 66.5 x 58.4 x 39.6 5.1 cm 26.7 cm 14.3 kg 12.7 kg N/A -40/9° C IP57 C IP57 DEF STAN 81-41/STANAG 4280 * 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	S ■ 1620M S ■ * 1630
1630 70.4 x 53.3 x 39.4 79.5 x 61.5 x 44.4 8.3 cm 30.8 cm 16.33 kg 14.06 kg 159 kg -40/99 °C 1P67 • DEF STAN 81-41/STANAG 4280 • 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	S • 1630
1640 60.2 x 61 x 35.3 69.1 x 69.9 x 41.4 5.1 cm 30.2 cm 17.24 kg 15.42 kg 166 kg -40 / 9° C 1P67 • DEF STAN 81-41/STANAG 4280 • ATA 300 • MIL C-4150.0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	
1650 72.2 x 44.2 x 27 80.1 x 52.1 x 31.7 4.6 cm 22.5 cm 12.73 kg 10.9 kg 82.1 kg -40/99°C IP67 • MIL C-4150.3 • DEF STAN 81-41/STANAG 4280 • ATA 300 0 0 S 0 0 1660 71.6 x 50.2 x 44.8 80 x 58.1 x 48.3 8.9 cm 35.9 cm 19.1 kg 15.5 kg 159 kg -23.3 / 99°C IP67 • DEF STAN 81-41/STANAG 4280 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	S <b>1640</b>
1660 71.6 x 50.2 x 44.8 80 x 58.1 x 48.3 8.9 cm 35.9 cm 19.1 kg 15.5 kg 159 kg -23.3 / 99° C IP67 • DEF STAN 81-41/STANAG 4280 0 0 0 0 0 1 0 0 0 1 0 0 0 0 0 0 0 0 0	<b>_</b>
1600 71.5 x 502.2 x 44.8 80 x 58.1 x 48.3 8.9 cm 35.9 cm 19.1 kg 13.5 kg 159 kg -22.3 / 99 ° C - 167.0 DEF STAN 61-41/STANAG 4280 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	S <b>■*</b> 1650
1690 76.5 x 63.8 x 39 84.9 x 72.1 x 44.8 7.3 cm 30.8 cm 19.5 kg 15.42 kg 186 kg -40 / 99° C IP67 • DEF STAN 81-41/STANAG 4280 0 0 0 0 0 1730 86.4 x 61 x 31.8 cm 95.3 x 68.9 x 36.5 6.4 cm 25.4 cm 17.24 kg 13.61 kg 189 kg -40 / 99° C DEF STAN 81-41/STANAG 4280 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	S <b>■*</b> 1660
1730 86.4 x 61 x 31.8 cm 95.3 x 68.9 x 36.5 6.4 cm 25.4 cm 17.24 kg 13.61 kg 189 kg -40 / 99° C IP67 DEF STAN 81-41/STANAG 4280 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	S <b>1670</b>
1780 104.4 x 54.7 x 37.8 114 x 64.3 x 41.9 19.3 cm 18.5 cm 22.20 kg 17.42 kg 226.8 kg -40 / 99° C DEF STAN 81-41/STANAG 4280 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	S <b>■*</b> 1690
0340         45.7 x 45.7 x 45.7         52.1 x 52.1 x 48.9         11.4 cm         34.3 cm         13.5 kg         10.89 kg         100 kg         -40 / 99° C         IP67 • DEF STAN 81-41 /STANAG 4280         0	S 1730
0350         50.8 x 50.8 x 50.8 x 50.8         57.2 x 57 x 54         12.7 cm         38.1 cm         14.52 kg         11.79 kg         122 kg         -40 / 99° C         IP67 • DEF STAN 81-41 /STANAG 4280         0	S <b>■*</b> 1780
0370         61 x 61 x 61         67.3 x 67.3 x 64.1         12.7 cm         48.3 cm         18.6 kg         14.5 kg         211 kg         -40 / 99° C         IP67 • DEF STAN 81-41 /STANAG 4280         0         0         0           0450         Varies by drawer configuration         60.8 x 37.5 x 45.6         N/A         N/A         N/A         N/A         N/A         N/A         N/A         N/A	■ 0340
0450         Varies by drawer configuration         60.8 x 37.5 x 45.6         N/A         N/A         N/A         N/A         N/A         N/A         -	0 0350
configuration 66.6 x 37.5 x 45.6 N/A N/A 21.75 kg N/A N/A N/A	0 8* 0370
<b>0500</b> 88.8 x 46.9 x 64.1 101.5 x 59.6 x 72.8 5.7 cm 58.4 cm 26.58 kg 22.68 kg 354 kg -40 / 99° C -	S <b>0450</b>
	0 0500
<b>0550</b> 120.8 x 61.1 x 44.9 129.7 x 70 x 57.9 8.1 cm 36.8 cm 43.09 kg 35.92 kg 371.95 kg -40 / 99° C IP57	O <b>■ 0550</b>
1700 91 x 35.3 x 13.3 96 x 45.5 x 15.5 4.5 cm 8.6 cm 7.7 kg 6.64 kg 62.1 kg -40 / 99° C IP67 • MIL C-4150J • DEF STAN 81-41/STANAG 4280	S <b>■</b> * 1700
1720 106.2 x 34.5 x 13.5 113 x 40.8 x 15.9 4.4 cm 8.9 cm 10.5 kg 8.3 kg 73 kg -40 / 99° C DEF STAN 81-41/STANAG 4280 0	S <b>■*</b> 1720
1726 100.2 x 34.3 x 13.5 113 x 40.8 x 13.7 4.4 cm 6.7 cm 10.5 kg 6.5 kg 75 kg -40 / 97 ° C DEF 31AN 61-41/31 ANAG 4260 0 0	
1750 128 x 33.9 x 13.5 142.4 x 40.8 x 15.6 4.4 cm 8.9 cm 12.1 kg 9.5 kg 85 kg -40 / 99° C IP67 • DEF STAN 81-41/STANAG 4280 0	S <b>=</b> * 1720
1770 138.6 x 39.6 x 21.9 145.8 x 46.9 x 28.5 4.8 cm 17.1 cm 18.8 kg 16.3 kg 127.01 kg N/A -	S ■* 1740 S ■* 1750
1780 104.4 x 54.7 x 37.8 114 x 64.3 x 41.9 19.3 cm 18.5 cm 22.20 kg 17.4 kg 226.8 kg -40 / 99° C DEF STAN 81-41/STANAG 4280 0	

PROTECTOR CASE™ COLOURS AVAILABLE




















\*Other colours and configurations available upon minimum quantities. Check with your Customer Service representative for further details.

# CASE ACCESSORIES



Check how to install all accessories through our easy step-by-step Tutorial videos

Lid Organisers






TrekPak™ Dividers




Padded Dividers



Dividers

Yellow Padded EZ-Click Molle Panel



Shoulder Straps

# TSA Locks and humidity indicators, Peli™ offers a broad range of case accessories.



Peli Desiccant (Silica Gel)

TSA Lock



From custom nameplates and padded shoulder straps, to

Nameplates



Card Holder Caster Wheel Kit





Pallet Riser

Refer to www.peli.com for

for each case model

specific accessories available

Lid Stays

22 PELI CASES CATALOGUE PELI CASES CATALOGUE 23

# LEARN MORE ABOUT + OUR PRODUCTS







www.peli.com

www.pelicatalogue.com

www.peli.com/webinars







#### EMEAI / www.peli.com

**EUROPE, MIDDLE EAST** & AFRICA HEADQUARTERS PELI PRODUCTS, S.L.U. C/ Provença, 388 Planta 7 08025 • Barcelona, Spain Tel +34 934 674 999

FRANCE PELI PRODUCTS FRANCE S.A.S. 20/22 Rue des Petits Hôtels 75010 Paris, France Tel +33 (0)1 44 83 95 63

UK ~ PELI HARDIGG UK Unit 4, Brookfield Industrial Estate Leacon Road Ashford Kent TN23 4TU Tel + 44 (0) 1233 895 895

PELI PRODUCTS GERMANY GmbH Neudorfer Strasse 285 C 09474 Crottendorf Germany Tel +49 (0)37344 313999

DENMARK PELI PRODUCTS DENMARK APS Midtermolen 1, 2, tv. 2100 Copenhagen, Denmark Tel: +34 934 674 999

**NETHERLANDS** PELI PRODUCTS NETHERLANDS B.V. Basisweg, 10 1043AP Amsterdam, The Netherlands Tel +34 934 674 999

PELI PRODUCTS ITALY S.R.L. Viale Monte Nero, 84 20135 Milano, Italy Tel +34 934 674 999

**POLAND** PELI PRODUCTS POLAND SP. Z O.O. ul. Stary Rynek 38-39 61-772 Poznan, Poland Tel +34 934 674 999

PELICAN PRODUCTS FZE JAFZA One Building A office 1511/1512 Jebel Ali Free Zone gate 5 P.O.Box 261008 Dubai - United Arab Emirates Tel +971 4 8876550

PELICAN PRODUCTS AND SERVICES INDIA PVT. LTD Level "4", Augusta Point, Sector-53, Golf Course Road, Gurgaon 122002 Haryana, India Tel +91 124 4354148

#### U.S.A.

U.S.A. & GLOBAL HEADQUARTERS 23215 Early Avenue Torrance, CA 90505 USA Tel 310.326.4700 800.473.5422 (Outside CA)

\* We also have offices in Canada, Japan, China, Australia and South Korea

#### INJECTION MOULDED CASES - PELI LIMITED LIFETIME\* GUARANTEE

Peli Products, S.L.U. ("Peli") guarantees its injection moulded products for a lifetime\* against breakage or defects in workmanship. Peli™ injection molded cases are guaranteed to be watertight to a depth of 3.3 feet (1 meter) for 30 minutes (IP 67) if properly closed with undamaged o-ring in place unless otherwise stated. To the extent permitted by law, Peli's liability is limited to the case and not its contents or foam. All warranty claims of any nature are barred if the case has been altered, damaged or in any way physically changed, or subjected to abuse, misuse, negligence or accident.

For complete warranty details, see www.peli.com/guarantee

\* Lifetime Guarantee not applicable where prohibited by law.

#### Distributed by:









©2023 Peli Products, S.L.U. All trademarks are registered and/or unregistered trademarks of Peli Products, S.L.U., its parent, subsidiaries and/or affiliates. All details included in this catalogue are correct when printed but for most updated information please visit www.peli.com and www.pelicatalogue.com. Part No. 0030-000-101E OCT 23



Check out our latest posts on Peli Cases, get to know our Pro Users and take part in our different



