

# **Certificate of Test Compliance**

**Worked Performed For:** 

Pelican Products 23215 Early Ave. Tustin, CA 90505 Job No. 10608 Contract No. N/A Purchase Order No. 4500341642 Date 07/03/2025

## **Dry Heat Test**

### **Test Requirements:**

Kelly Space & Technology Inc. certifies that the Case, Part No. M40 – 6.80" L x 5.00" W x 2.60" H was subjected to dry heat per DEF STAN 81-41 Part 3/4 par. 14 & 17.

## **Pre-Conditioning:**

Temperature:  $25^{\circ}\text{C} \pm 10^{\circ}\text{C}$ Humidity:  $60\% \pm 15\%$ 

Duration: 16 hours or until specimen has reached temperature stabilization (whichever is

the shortest period)

**Testing:** 

Temperature:  $71 \pm 2^{\circ}C$ 

Humidity: Not to exceed 75%

Duration:  $48 \pm 1$  hours

The testing was completely and correctly performed in accordance with DEF STAN 81-41 Part 3/4 par. 14 & 17 specifications. Complete test results are documented in Kelly Space & Technology, Inc. Test Report No. 10608.

#### **Test Summary:**

Place the test specimen in a test chamber on the face on which it normally is expected to be transported or stored. Install a thermocouple on the test specimen. Maintain the chamber at  $25^{\circ}\text{C} \pm 10^{\circ}\text{C}$  and  $60\% \pm 15\%$  relative humidity for 16 hours or until the specimen has reached temperature stabilization (test specimen temperature within tolerance of the chamber temperature).

Increase the chamber temperature to  $71^{\circ}C \pm 2^{\circ}C$  at rate not to exceed  $3^{\circ}C$  per minute. Humidity is not to exceed 75%. Maintain the chamber at these conditions for  $48 \pm 1$  hour. Return the chamber temperature to ambient conditions at a rate not to exceed  $3^{\circ}C$  per minute. Perform a visual examination and document all results. All testing was performed per the test requirements and test summary stated above. There was no visible damage to the test specimens upon completion of testing.

ISO Certification		
Available Upon	Prepared by:	
Request		Omar Ruelas, Test Engineer I
	Approved By:	
		Farrah Morones, Environmental Test
		Operations Manager