



## Certificate of Test Compliance

**Worked Performed For:**

**Pelican Products**  
**23215 Early Ave.**  
**Tustin, CA 90505**

**Job No. 10583**

**Contract No. N/A**

**Purchase Order No. 4500275880 ; 4500273821**

**Date 03/31/2023**

### Low Temperature Test

**Test Requirements:**

Kelly Space & Technology Inc. certifies that the Case, Part No. 1300 - 10.67" L x 9.76" W x 6.89" H was subjected to Low Temperature per DEF STAN 81-41 Part 3/4 Par. 21.

**Temperature:**  $-51^{\circ}\text{C} \pm 2^{\circ}\text{C}$

**Duration:**  $16 \pm 0.5$  hours after specimen has reached test temperature or 7 days  $\pm 1$  hour if time required for the package to attain the temperature cannot be assessed.

The testing was completely and correctly performed in accordance with DEF STAN 81-41 Part 3/4 Par. 21. specifications. Complete test results are documented in Kelly Space & Technology, Inc. Test Report No. 10583.

**Test Summary:**

Place the test specimen in a test chamber on the face on which it normally is expected to be transported or stored. Install a thermocouple on the test specimen, Decrease the chamber temperature to  $-51^{\circ}\text{C} \pm 2^{\circ}\text{C}$  at a rate not to exceed  $3^{\circ}\text{C}$  per minute. Maintain the chamber at  $-51^{\circ}\text{C} \pm 2^{\circ}\text{C}$  for either:

- 1)  $16 \pm 0.5$  hours after specimen has reached test temperature or
- 2) 7 days  $\pm 1$  hour if time required for the complete package to attain the temperature cannot be assessed.

Return the chamber temperature to ambient conditions at a rate not to exceed  $3^{\circ}\text{C}$  per minute.

Perform visual examination. The package is considered to have failed if it is unserviceable or is affected in any way which would potentially cause the test specimen to become unserviceable.

All testing was performed per the test requirements and test summary stated above. There was no visible damage to the test specimen upon completion of testing.

ISO Certification

Available Upon  
Request

**Prepared by:**

\_\_\_\_\_  
Farrah Morones, Environmental Test  
Operations Manager

**Approved By:**

\_\_\_\_\_  
Mike Gallo, CEO & President



## Certificate of Test Compliance

**Worked Performed For:**

**Pelican Products**  
**23215 Early Ave.**  
**Tustin, CA 90505**

**Job No. 10583**

**Contract No. N/A**

**Purchase Order No. 4500275880 ; 4500273821**

**Date 04/07/2023**

### Low Temperature Test

**Test Requirements:**

Kelly Space & Technology Inc. certifies that the Case, Part No. 1595 - 17.79" L x 10.63" W x 28.51" H was subjected to Low Temperature per DEF STAN 81-41 Part 3/4 Par. 21.

**Temperature:**  $-51^{\circ}\text{C} \pm 2^{\circ}\text{C}$

**Duration:**  $16 \pm 0.5$  hours after specimen has reached test temperature or 7 days  $\pm 1$  hour if time required for the package to attain the temperature cannot be assessed.

The testing was completely and correctly performed in accordance with DEF STAN 81-41 Part 3/4 Par. 21.specifications. Complete test results are documented in Kelly Space & Technology, Inc. Test Report No. 10583.

**Test Summary:**

Place the test specimen in a test chamber on the face on which it normally is expected to be transported or stored. Install a thermocouple on the test specimen, Decrease the chamber temperature to  $-51^{\circ}\text{C} \pm 2^{\circ}\text{C}$  at a rate not to exceed  $3^{\circ}\text{C}$  per minute. Maintain the chamber at  $-51^{\circ}\text{C} \pm 2^{\circ}\text{C}$  for either:

- 1)  $16 \pm 0.5$  hours after specimen has reached test temperature or
- 2) 7 days  $\pm 1$  hour if time required for the complete package to attain the temperature cannot be assessed.

Return the chamber temperature to ambient conditions at a rate not to exceed  $3^{\circ}\text{C}$  per minute.

Perform visual examination. The package is considered to have failed if it is unserviceable or is affected in any way which would potentially cause the test specimen to become unserviceable.

All testing was performed per the test requirements and test summary stated above. There was no visible damage to the test specimen upon completion of testing.

ISO Certification

Available Upon  
Request

**Prepared by:**

\_\_\_\_\_  
Farrah Morones, Environmental Test  
Operations Manager

**Approved By:**

\_\_\_\_\_  
Mike Gallo, CEO & President



## Certificate of Test Compliance

**Worked Performed For:**

**Pelican Products**  
23215 Early Ave.  
Tustin, CA 90505

**Job No. 10583**

**Contract No. N/A**

**Purchase Order No. 4500275880 ; 4500273821**

**Date 03/31/2023**

### Low Temperature Test

**Test Requirements:**

Kelly Space & Technology Inc. certifies that the Case, Part No. 1700 - 38.45" L x 16.38" W x 6.14" H was subjected to Low Temperature per DEF STAN 81-41 Part 3/4 Par. 21.

**Temperature:**  $-51^{\circ}\text{C} \pm 2^{\circ}\text{C}$

**Duration:**  $16 \pm 0.5$  hours after specimen has reached test temperature or 7 days  $\pm 1$  hour if time required for the package to attain the temperature cannot be assessed.

The testing was completely and correctly performed in accordance with DEF STAN 81-41 Part 3/4 Par. 21.specifications. Complete test results are documented in Kelly Space & Technology, Inc. Test Report No. 10583.

**Test Summary:**

Place the test specimen in a test chamber on the face on which it normally is expected to be transported or stored. Install a thermocouple on the test specimen, Decrease the chamber temperature to  $-51^{\circ}\text{C} \pm 2^{\circ}\text{C}$  at a rate not to exceed  $3^{\circ}\text{C}$  per minute. Maintain the chamber at  $-51^{\circ}\text{C} \pm 2^{\circ}\text{C}$  for either:

- 1)  $16 \pm 0.5$  hours after specimen has reached test temperature or
- 2) 7 days  $\pm 1$  hour if time required for the complete package to attain the temperature cannot be assessed.

Return the chamber temperature to ambient conditions at a rate not to exceed  $3^{\circ}\text{C}$  per minute.

Perform visual examination. The package is considered to have failed if it is unserviceable or is affected in any way which would potentially cause the test specimen to become unserviceable.

All testing was performed per the test requirements and test summary stated above. There was no visible damage to the test specimen upon completion of testing.

ISO Certification

Available Upon  
Request

**Prepared by:**

\_\_\_\_\_  
Farrah Morones, Environmental Test  
Operations Manager

**Approved By:**

\_\_\_\_\_  
Mike Gallo, CEO & President



## Certificate of Test Compliance

**Worked Performed For:**

**Pelican Products**  
23215 Early Ave.  
Tustin, CA 90505

**Job No. 10583**

**Contract No. N/A**

**Purchase Order No. 4500275880 ; 4500273821**

**Date 03/31/2023**

### Low Temperature Test

**Test Requirements:**

Kelly Space & Technology Inc. certifies that the Case, Part No. 1720 - 44.48" L x 16.08" W x 6.25" H was subjected to Low Temperature per DEF STAN 81-41 Part 3/4 Par. 21.

**Temperature:**  $-51^{\circ}\text{C} \pm 2^{\circ}\text{C}$

**Duration:**  $16 \pm 0.5$  hours after specimen has reached test temperature or 7 days  $\pm 1$  hour if time required for the package to attain the temperature cannot be assessed.

The testing was completely and correctly performed in accordance with DEF STAN 81-41 Part 3/4 Par. 21. specifications. Complete test results are documented in Kelly Space & Technology, Inc. Test Report No. 10583.

**Test Summary:**

Place the test specimen in a test chamber on the face on which it normally is expected to be transported or stored. Install a thermocouple on the test specimen, Decrease the chamber temperature to  $-51^{\circ}\text{C} \pm 2^{\circ}\text{C}$  at a rate not to exceed  $3^{\circ}\text{C}$  per minute. Maintain the chamber at  $-51^{\circ}\text{C} \pm 2^{\circ}\text{C}$  for either:

- 1)  $16 \pm 0.5$  hours after specimen has reached test temperature or
- 2) 7 days  $\pm 1$  hour if time required for the complete package to attain the temperature cannot be assessed.

Return the chamber temperature to ambient conditions at a rate not to exceed  $3^{\circ}\text{C}$  per minute.

Perform visual examination. The package is considered to have failed if it is unserviceable or is affected in any way which would potentially cause the test specimen to become unserviceable.

All testing was performed per the test requirements and test summary stated above. There was no visible damage to the test specimen upon completion of testing.

ISO Certification

Available Upon  
Request

**Prepared by:**

Farrah Morones, Environmental Test  
Operations Manager

**Approved By:**

Mike Gallo, CEO & President



## Certificate of Test Compliance

**Worked Performed For:**

**Pelican Products**  
23215 Early Ave.  
Tustin, CA 90505

**Job No.** 10583

**Contract No.** N/A

**Purchase Order No.** 4500275880 ; 4500273821

**Date** 03/31/2023

### Low Temperature Test

**Test Requirements:**

Kelly Space & Technology Inc. certifies that the Case, Part No. 1750 - 53.06" L x 10.05" W x 5.13" H was subjected to Low Temperature per DEF STAN 81-41 Part 3/4 Par. 21.

**Temperature:**  $-51^{\circ}\text{C} \pm 2^{\circ}\text{C}$

**Duration:**  $16 \pm 0.5$  hours after specimen has reached test temperature or 7 days  $\pm 1$  hour if time required for the package to attain the temperature cannot be assessed.

The testing was completely and correctly performed in accordance with DEF STAN 81-41 Part 3/4 Par. 21.specifications. Complete test results are documented in Kelly Space & Technology, Inc. Test Report No. 10583.

**Test Summary:**

Place the test specimen in a test chamber on the face on which it normally is expected to be transported or stored. Install a thermocouple on the test specimen, Decrease the chamber temperature to  $-51^{\circ}\text{C} \pm 2^{\circ}\text{C}$  at a rate not to exceed  $3^{\circ}\text{C}$  per minute. Maintain the chamber at  $-51^{\circ}\text{C} \pm 2^{\circ}\text{C}$  for either:

- 1)  $16 \pm 0.5$  hours after specimen has reached test temperature or
- 2) 7 days  $\pm 1$  hour if time required for the complete package to attain the temperature cannot be assessed.

Return the chamber temperature to ambient conditions at a rate not to exceed  $3^{\circ}\text{C}$  per minute.

Perform visual examination. The package is considered to have failed if it is unserviceable or is affected in any way which would potentially cause the test specimen to become unserviceable.

All testing was performed per the test requirements and test summary stated above. There was no visible damage to the test specimen upon completion of testing.

ISO Certification

Available Upon  
Request

**Prepared by:**

Farrah Morones, Environmental Test  
Operations Manager

**Approved By:**

Mike Gallo, CEO & President



## Certificate of Test Compliance

**Worked Performed For:**

**Pelican Products**  
23215 Early Ave.  
Tustin, CA 90505

**Job No. 10583**

**Contract No. N/A**

**Purchase Order No. 4500275880 ; 4500273821**

**Date 03/31/2023**

### Low Temperature Test

**Test Requirements:**

Kelly Space & Technology Inc. certifies that the Case, Part No. 1755 – 57.81" L x 16.71" W x 8.86" H was subjected to Low Temperature per DEF STAN 81-41 Part 3/4 Par. 21.

**Temperature:**  $-51^{\circ}\text{C} \pm 2^{\circ}\text{C}$

**Duration:**  $16 \pm 0.5$  hours after specimen has reached test temperature or 7 days  $\pm 1$  hour if time required for the package to attain the temperature cannot be assessed.

The testing was completely and correctly performed in accordance with DEF STAN 81-41 Part 3/4 Par. 21.specifications. Complete test results are documented in Kelly Space & Technology, Inc. Test Report No. 10583.

**Test Summary:**

Place the test specimen in a test chamber on the face on which it normally is expected to be transported or stored. Install a thermocouple on the test specimen, Decrease the chamber temperature to  $-51^{\circ}\text{C} \pm 2^{\circ}\text{C}$  at a rate not to exceed  $3^{\circ}\text{C}$  per minute. Maintain the chamber at  $-51^{\circ}\text{C} \pm 2^{\circ}\text{C}$  for either:

- 1)  $16 \pm 0.5$  hours after specimen has reached test temperature or
- 2) 7 days  $\pm 1$  hour if time required for the complete package to attain the temperature cannot be assessed.

Return the chamber temperature to ambient conditions at a rate not to exceed  $3^{\circ}\text{C}$  per minute.

Perform visual examination. The package is considered to have failed if it is unserviceable or is affected in any way which would potentially cause the test specimen to become unserviceable.

All testing was performed per the test requirements and test summary stated above. There was no visible damage to the test specimen upon completion of testing.

ISO Certification

Available Upon  
Request

**Prepared by:**

\_\_\_\_\_  
Farrah Morones, Environmental Test  
Operations Manager

**Approved By:**

\_\_\_\_\_  
Mike Gallo, CEO & President