

Certificate of Test Compliance

Worked Performed For:

Pelican Products 23215 Early Ave. Tustin, CA 90505 Job No. 10608 Contract No. N/A Purchase Order No. 4500341642 Date 07/03/2025

Random Vibration Test

Test Requirements:

Kelly Space & Technology Inc. certifies that the Case, Part No. M40 Micro Case – 6.80" L x 5.00" W x 2.60" H was subjected to random vibration per I DEF STAN 81-41 Part 3/4 Par. 24.

Pre-Conditioning:

Temperature: $25^{\circ}\text{C} \pm 10^{\circ}\text{C}$ Humidity: $60\% \pm 15\%$

Duration: 16 hours or until specimen has reached temperature stabilization (whichever is the shortest

period)

Testing:

Test Frequency: 5 to 350 Hz Test Level: Noted Below Vibration Type: Sinusoidal

Orientations: 3 (Front/Back, Side/Side, Top/Bottom)

The testing was completely and correctly performed in accordance with DEF STAN 81-41 Part 3/4 Par. 24 specifications. Complete test results are documented in Kelly Space & Technology, Inc. Test Report No. 10608.

Test Summary:

Install the test specimens to the vibration test setup in the first orientation. Photograph the test setup.

The cases shall be vibrated for 2 hours in each of three mutually perpendicular axes at a vibration amplitude of $(\pm 6 \text{mm peak from 5 to 9 Hz})$ and $(\pm 2 \text{ g peak from 9 to 350 Hz})$ and a continuous logarithmic rate of 0.75 ± 0.25 octave per minute. Perform a visual examination and document all results.

All testing was performed per the test requirements and test summary stated above. There was no visible damage to the test specimens upon completion of testing.

ISO Certification		
Available Upon	Prepared by:	
Request		Omar Ruelas, Test Engineer I
	Approved By:	
		Farrah Morones, Environmental Test
		Operations Manager