

DATE: NOVEMBER 1, 2011

TITLE: PELICAN UPGRADES THE PELICAN 2360 LED FLASHLIGHT

PRODUCTS AFFECTED: PELICAN 2360 LED FLASHLIGHT

INTRODUCTION:

To incorporate the latest LED technology and features, the 2360 LED flashlight has been upgraded with the following elements while maintaining the same price:



- Secure pocket clip
- Matte finish

Increased wall thickness for durability



Less sensitive tail cap switch

9 New and Improved Features
Same Price

	High	Low
LIGHT SOURCE	LED	
BATTERIES	2 AA Alkaline (Included)	
CHARGE TIME	N/A	
VOLTAGE	3	
LENGTH	6.2" (15.7 cm)	
WEIGHT w/ BATTERIES	5.4 oz. (0.15 kg)	
WEIGHT w/o BATTERIES	3.7 oz. (0.1 kg)	

FL1 STANDARD	High	Low
LIGHT OUTPUT	110 LUMENS	10 LUMENS
RUNTIME (hours/min)	2h	40h
BEAM DISTANCE (meters)	158m	49m
PEAK BEAM INTENSITY (candela)	6242cd	615cd
WATER RESISTANT	IPX4	

High/Low Brightness Setting
(Not featured in previous model)

2 - AA Batteries Now Included
(Not included with previous model)

Nearly 15% Brighter – 110 Lumens in High
(Previous model produced 94)

Increased Beam Distance – 158M in High Setting
(Previous model was 139m)

Increased Peak Beam Intensity – 6242cd in High Setting
(Previous model was 4893cd)

New ANSI Specs

