Technical Bulletin



DATE: July 7, 2010

TITLE: CLASS I II III, DIV. 1, GRPS. ABCDEFG - SAFETY APPROVAL UPGRADES FOR THE PELICAN™ 2410 STEALTHLITE™ AND 3610 LITTLE ED™ RECOIL™ LED

PRODUCTS AFFECTED: 2410 StealthLite Recoil LED, 2410PL StealthLite Recoil LED, 3610 Little Ed Recoil LED, 3610PL Little Ed Recoil LED

DETAILS:

The Pelican 2410 StealthLite LED Recoil and 3610 Little Ed Recoil LED now feature:

- Upgraded safety approvals:



Edison Testing Labs
Class I II III Div. 1 Grps.
ABCDEFG Operating
Temp. Class T4



2410 StealthLite Recoil



International Electrotechnical Commission

ITS.09.0017X Ex ia IIC T4 Ga, Ex ia IIIC T83°C Da IP66

For more information on safety approvals please follow this link.

New ANSI FL1specifications:



Total Light Output

Run Time

Beam Distance Peak Beam Intensity



3610 Little Ed

- New Part Numbers:

2410 StealthLite Recoil LED

- 2410-015-110
- 2410-015-245
- 2410-015-247

3610 Little Ed Recoil LED

- 3610-015-110
- 3610-015-245
- 3610-015-247

